




MATHARU
Industries Pvt Ltd. (INDIA)

Model:- MO-0117

MULTI SPEED

GEAR DRIVE

ROTAVATOR



Model:- MO-0117

MATHARU **Rotavator**

Introduction: -

We are an ISO certified organization engaged in manufacturing, supplying and exporting highly durable Agricultural Rotavator. The offered range of equipment is fabricated by our engineers employing advanced techniques and methodologies. Offered Agricultural Rotavator can be used on every type of soil. This is a rotavator that is perfect for tractor from 30 to 65 HP. Clients can avail the offered rotavator from us at cost effective prices.

Benefits of Matharu Rotavator: -

- *It prepares the field for seeding in first go only.*
- *Its gear makes it more robust and powerful than conventional chain Rotavators.*
- *Saves more time and Prevents the tractor from wear and tear.*
- *More fuel efficient and preserves the moisture in the soil.*
- *Performs well in every type of soil whether wet or dry.*
- *Mixes the remains of the previous harvest in the soil, which fertilizes the farm.*
- *It is very helpful in Sugarcane, Banana, Vegetables and Rice farms.*



Model:- MO-0117

MATHARU

Rotavator

Special features: -

- *Specially Designed Tapered Blades made of High Quality Steel.*
- *Gear helps it to work Smoothly & Efficiently.*
- *Export Quality Heavy Duty Gear Box.*
- *Nuts & Bolts made of High Tensile Steel.*
- *Every part made with Computerized CNC machines.*
- *Saves more time and prevents the tractor from wear and tear.*
- *Export Quality Heavy Duty Gear Box.*
- *High Tensile Nut Bolts Used.*
- *Adjustable Trailing Board.*
- *Side Disk available as Optional.*
- *PTO Shaft Safety Cover.*
- *High Quality blades for Longer Life.*
- *Heavy Duty Steel Body made of Square Pipe.*
- *Large Sieve Area for Optimum Grain Cleaning.*



MATHARU

Rotavator

Model by Size	5 Feet	5.5 Feet	6 Feet	7 Feet	8 Feet
Width					
Height					
Length					
Working Width	1.44 mtr.	1.66 mtr.	1.88 mtr.	2.11 mtr.	2.34 mtr.
Working Depth	5"	5"	6"	6"	7"
HP Required	30-45	30-45	40-55	45-60	55-65
Number of Flanges	Six	Seven	Eight	Nine	Ten
Number of Blades	36	42	48	54	60
PTO Speed (RPM)	540	540	540	540	540
Rotor Speed	270	270	270	270	270
Weight					

Note: Technical Specification may change/update without any prior notice.

Thanks for your efforts



MATHARU INDUSTRIES Pvt. Ltd.

Ferozepur Road, FARIDKOT- 151203, Punjab, INDIA

Phone. +91 93577 50577, +91 93577 50576

Email: info@matharugroup.com

www.matharugroup.com

- ❖ The manufacturer reserves the right to make change and/or improvements in specification without prior notice.
- ❖ *Performance figures are approximate and for general guidance only. Guidance is based on drying principles, computer simulations and field results.
- ❖ Factors including crop type, crop condition, excessive admixture and weather conditions may affect the performance.